

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PHR2-160 GRADE II RTXBB-NA BLACK</b>
<b>Transtex Product Code:</b>	<b>908221</b>
<b>Product Construction:</b>	<b>2 Ply Filament Polyester &amp; Nylon Carcass, Black Grade II Rubber x Bare</b>
<b>Color:</b>	<b>Black</b>
<b>Compound Formulation:</b>	<b>Grade II Rubber</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.255 +/- 0.025</b>
<b>mm:</b>	<b>6.5 +/- 0.6</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>1.07 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>5.2 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>160 lbs./in. / 28 N/mm. @ 2%</b>
<b>Top Cover Surface:</b>	<b>Rough Top</b>
<b>Bottom Cover Surface:</b>	<b>Bare RFL Treated Fabric</b>
<b>Minimum Pulley Diameter:</b>	<b>4 inches / 102 mm.</b>
<b>Temperature Range:</b>	<b>-20° F to 225°F (-29° F to 107°C)</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>RMA Grade II Covers</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>1.0, Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.22, Nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm. (other widths available)</b>
<b>Typical Applications:</b>	<b>Slider Bed, Incline/Declines &gt;5°</b>
<b>Specification Date:</b>	<b>April 01, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to its products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to its use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.