

TRANSTEX PRODUCT SPECIFICATIONS

Product Specification:	FTP2-100 OFR CXF-NA WHITE
Transtex Product Code:	908829
Product Construction:	2 ply spun Polyester with a white food grade, oil and fat resistant, PVC top cover
Color:	White
Compound Formulation:	White Food Grade, oil and fat resistant PVC Cover and Impregnated Carcass
Nominal Overall Gauge, inches:	0.115 +/- 0.01
mm:	2.9 +/- 0.25
Nominal Weight, in lbs/ft²:	0.8 +/- 10%
in kg/m²:	3.9 +/- 10%
Rated Working Tension:	100 lbs./in. / 17.5 N/mm. @ 1.5%
Top Cover Surface:	PVC Smooth Cover
Bottom Cover Surface:	Friction
Minimum Pulley Diameter:	1.5 inches / 38 mm.
Temperature Range:	0° to 180° F / -18° to 82°C
Transverse Rigidity:	N/A
Special Standards:	Oil Resistant Food Grade
Cover Coefficient of Friction, Steel:	0.9 nominal
Bottom Coefficient of Friction, Steel:	0.8 nominal
Production Width(s):	72 inches / 1829 mm.
Typical Applications:	Processing of meat, fruits, vegetables and other food where oils and fats are present
Specification Date:	May 26, 2009

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.