

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PVC120 P CTXF-NA BLACK</b>
<b>Transtex Product Code:</b>	<b>908760</b>
<b>Product Construction:</b>	<b>Single ply 120 lb interwoven polyester carcass with a black PVC top cover.</b>
<b>Color:</b>	<b>Black</b>
<b>Compound Formulation:</b>	<b>Black low temperature PVC Cover / Black PVC impregnated carcass</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.240 +/- 0.01</b>
<b>mm:</b>	<b>6.1 +/- 0.25</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>0.85 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>4.1 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>120 lbs./in. / 21 N/mm. @ 1.5%</b>
<b>Top Cover Surface:</b>	<b>Crescent Top</b>
<b>Bottom Cover Surface:</b>	<b>Friction</b>
<b>Minimum Pulley Diameter:</b>	<b>2 inches / 51 mm.</b>
<b>Temperature Use Range:</b>	<b>0° to 180° F. / -18° to 82°C.</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>N/A</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>1.1, Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.8, nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm.</b>
<b>Typical Applications:</b>	<b>General conveying, sorting, picking, material handling, moderate incline/decline applications.</b>
<b>Specification Date:</b>	<b>September 10, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to its products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to its use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.