

TRANSTEX PRODUCT SPECIFICATIONS

Product Specification:	PVC120 OFR CTXF-NA WHITE
Transtex Product Code:	908757
Product Construction:	Single Ply Interwoven Polyester carcass with a white OFR PVC top cover.
Color:	White
Compound Formulation:	White oil and fat resistant PVC impregnation and cover.
Nominal Overall Gauge, inches:	0.220 +/- 0.01
mm:	5.6 +/- 0.25
Nominal Weight, in lbs/ft²:	0.85 +/- 10%
in kg/m²:	4.1 +/- 10%
Rated Working Tension:	120 lbs./in. / 21 N/mm. @ 1.5%
Top Cover Surface:	Crescent Top
Bottom Cover Surface:	Friction
Minimum Pulley Diameter:	2 inches / 51 mm.
Temperature Range:	0° to 180° F. / -18° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	Food Grade
Cover Coefficient of Friction, Steel:	1.3 Nominal
Bottom Coefficient of Friction, Steel:	0.8 nominal
Production Width(s):	72 inches / 1829 mm.
Typical Applications:	Incline/decline applications and processing of meat, fruits, vegetables and other food where oils and fats are present
Specification Date:	June 12, 2009

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.