

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PVC 200 O/M CxC Black</b>
<b>Transtex Product Code:</b>	<b>908029</b>
<b>Product Construction:</b>	<b>Single ply 200 lb interwoven polyester with black PVC top and bottom covers.</b>
<b>Color:</b>	<b>Black</b>
<b>Compound Formulation:</b>	<b>Fire resistant PVC Covers and PVC Impregnated Carcass</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.240 +/- 0.01</b>
<b>mm:</b>	<b>6.1 +/- 0.25</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>1.6 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>7.8 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>200 lbs./in. / 35 N/mm. @ 1.5%</b>
<b>Top Cover Surface:</b>	<b>Smooth black PVC</b>
<b>Bottom Cover Surface:</b>	<b>Smooth black PVC</b>
<b>Minimum Pulley Diameter:</b>	<b>4 inches / 102 mm.</b>
<b>Temperature Range:</b>	<b>0° to 180° F. / -18° to 82°C.</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>Fire resistant to MSHA 2G. Static conductive to OSHA 29 CFR.</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>0.83 Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.83 Nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm.</b>
<b>Typical Applications:</b>	<b>Bulk handling, material handling, live roller applications</b>
<b>Specification Date:</b>	<b>June 11, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.