

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PVC200 P CXF-NA BLACK</b>
<b>Transtex Product Code:</b>	<b>908775</b>
<b>Product Construction:</b>	<b>Single ply 200 lb interwoven Polyester with black PVC cover.</b>
<b>Color:</b>	<b>Black</b>
<b>Compound Formulation:</b>	<b>PVC Cover / PVC Impregnated Carcass</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.200 +/- 0.01</b>
<b>mm:</b>	<b>5.1 +/- 0.25</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>1.3 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>6.3 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>200 lbs./in. / 35 N/mm. @ 1.5%</b>
<b>Top Cover Surface:</b>	<b>PVC smooth cover</b>
<b>Bottom Cover Surface:</b>	<b>Friction</b>
<b>Minimum Pulley Diameter:</b>	<b>4 inches / 102 mm.</b>
<b>Temperature Range:</b>	<b>0° to 180° F. / -18° to 82°C.</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>N/A</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>0.8 Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.8 Nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm.</b>
<b>Typical Applications:</b>	<b>General conveying, sorting, material handling, picking, transfer conveyors</b>
<b>Specification Date:</b>	<b>June 12, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.