

TRANSTEX PRODUCT SPECIFICATIONS

Product Specification:	PVC 350 O/M CxC Black
Transtex Product Code:	908732
Product Construction:	Solid woven polyester carcass with black PVC top and bottom covers.
Color:	Black
Compound Formulation:	Fire resistant PVC Covers and PVC Impregnated Carcass
Nominal Overall Gauge, inches:	0.305 +/- 0.01
mm:	7.7 +/- 0.25
Nominal Weight, in lbs/ft²:	2.0 +/- 10%
in kg/m²:	9.8 +/- 10%
Rated Working Tension:	350 lbs./in. / 61 N/mm. @ 1.5%
Top Cover Surface:	Smooth
Bottom Cover Surface:	Smooth
Minimum Pulley Diameter:	7 inches / 178 mm.
Temperature Range:	0° to 180° F. / -18° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	Fire resistant to MSHA 2G/ASTM D378. Static conductive to OSHA 29 CFR.
Cover Coefficient of Friction, Steel:	0.83 Nominal
Bottom Coefficient of Friction, Steel:	0.83 Nominal
Production Width(s):	72 inches / 1829 mm.
Typical Applications:	Bucket elevators, recycling, grain, feed & seed fertilizer, applications requiring good tear resistance.
Specification Date:	May 14, 2009

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.