

TRANSTEX PRODUCT SPECIFICATIONS

Product Specification:	PVC200 LT AR CXF-NA BLUE
Transtex Product Code:	908758
Product Construction:	Single ply 200 lb interwoven polyester with a blue PVC top cover.
Color:	Blue
Compound Formulation:	Blue premium abrasion resistant, low temp PVC impregnated carcass and cover.
Nominal Overall Gauge, inches:	0.200 +/- 0.01
mm:	5.1 +/- 0.25
Nominal Weight, in lbs/ft²:	1.3 +/- 10%
in kg/m²:	6.3 +/- 10%
Rated Working Tension:	200 lbs./in. / 35 N/mm. @ 1.5%
Top Cover Surface:	Smooth
Bottom Cover Surface:	Friction
Minimum Pulley Diameter:	4 inches / 102 mm.
Temperature Range:	-40° to 180° F. / -40° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	Rated low temperature to -40 deg F / C. Premium abrasion resistant covers.
Cover Coefficient of Friction, Steel:	0.8 Nominal
Bottom Coefficient of Friction, Steel:	0.8 Nominal
Production Width(s):	72 inches / 1829 mm.
Typical Applications:	Applications requiring low temperature and high abrasion resistance.
Specification Date:	September 21, 2009

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.