

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PF300 LT AR CXB-NA BLUE</b>
<b>Transtex Product Code:</b>	<b>908774</b>
<b>Product Construction:</b>	<b>300 lb interwoven polyester carcass with a blue PVC top cover.</b>
<b>Color:</b>	<b>Blue</b>
<b>Compound Formulation:</b>	<b>Blue premium abrasion resistant, low temp PVC cover/ low temp blue PVC Carcass</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.250 +/- 0.010</b>
<b>mm:</b>	<b>6.35 +/- 0.25</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>1.7 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>8.3 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>300 lbs./in. / 52.5 N/mm. @ 1.5%</b>
<b>Top Cover Surface:</b>	<b>Smooth</b>
<b>Bottom Cover Surface:</b>	<b>Brushed</b>
<b>Minimum Pulley Diameter:</b>	<b>7 inches / 178 mm.</b>
<b>Temperature Range:</b>	<b>-40° to 180° F. / -40° to 82°C.</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>Rated low temperature to -40 deg F / C. Premium abrasion resistant covers.</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>0.8, Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.4, nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm.</b>
<b>Typical Applications:</b>	<b>Applications requiring low temperature and high abrasion resistance.</b>
<b>Specification Date:</b>	<b>September 21, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.