

## TRANSTEX PRODUCT SPECIFICATIONS

<b>Product Specification:</b>	<b>PF120 LT AR CTXF-NA BLUE</b>
<b>Transtex Product Code:</b>	<b>908010</b>
<b>Product Construction:</b>	<b>Single Ply Interwoven Polyester with a blue abrasion resistant, low temp PVC top cover.</b>
<b>Color:</b>	<b>Blue</b>
<b>Compound Formulation:</b>	<b>Blue premium abrasion resistant, low temp PVC top cover/ low temp PVC Carcass</b>
<b>Nominal Overall Gauge, inches:</b>	<b>0.240 +/- 0.01</b>
<b>mm:</b>	<b>6.1 +/- 0.25</b>
<b>Nominal Weight, in lbs/ft<sup>2</sup>:</b>	<b>0.85 +/- 10%</b>
<b>in kg/m<sup>2</sup>:</b>	<b>4.1 +/- 10%</b>
<b>Rated Working Tension:</b>	<b>120 lbs./in. / 21 N/mm. @ 1.5%</b>
<b>Top Cover Surface:</b>	<b>Crescent top</b>
<b>Bottom Cover Surface:</b>	<b>Friction</b>
<b>Minimum Pulley Diameter:</b>	<b>2 inches / 51 mm.</b>
<b>Temperature Range:</b>	<b>-40° to 180° F. / -40° to 82°C.</b>
<b>Transverse Rigidity:</b>	<b>N/A</b>
<b>Special Standards:</b>	<b>Rated low temperature to -40 deg F / C. Premium abrasion resistant cover.</b>
<b>Cover Coefficient of Friction, Steel:</b>	<b>1.3 Nominal</b>
<b>Bottom Coefficient of Friction, Steel:</b>	<b>0.8 nominal</b>
<b>Production Width(s):</b>	<b>72 inches / 1829 mm.</b>
<b>Typical Applications:</b>	<b>Cold temperature, high abrasion applications</b>
<b>Specification Date:</b>	<b>July 23, 2009</b>

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.