

TRANSTEX PRODUCT SPECIFICATIONS

Product Specification:	PU120PH HCXF-NA RED
Transtex Product Code:	908894
Product Construction:	Single Ply Interwoven Polyester with a 2mm polyurethane top cover.
Color:	Red
Compound Formulation:	Thermoplastic Polyurethane (90 Shore A) Cover/ PVC OFR Carcass
Nominal Overall Gauge, inches:	0.220 +/- 0.01
mm:	5.6 +/- 0.25
Nominal Weight, in lbs/ft²:	1.3 +/- 10%
in kg/m²:	6.3 +/- 10%
Rated Working Tension:	120 lbs./in. / 21 N/mm. @ 1.5%
Top Cover Surface:	2 mm Smooth Cover
Bottom Cover Surface:	Friction
Minimum Pulley Diameter:	3 inches / 76 mm.
Temperature Range:	20° to 180° F. / -7° to 82°C.
Transverse Rigidity:	N/A
Special Standards:	N/A
Cover Coefficient of Friction, Steel:	1.0, nominal
Bottom Coefficient of Friction, Steel:	0.4, nominal
Production Width(s):	72 inches / 1829 mm.
Typical Applications:	Recycling, Metals, Stamping, Oil, and Chemical
Specification Date:	May 12, 2009

Forbo Movement Systems, Transtex Belting, does provide information, written and verbal, relative to it's products which it considers to be accurate and reliable. Such information is offered as a service only and is not an expression of warranty. Forbo Movement systems does not assume any liability whatsoever in regard to it's use. The buyer of Forbo Movement Systems, Transtex Belting products should determine for itself the suitability of such products for the particular purpose of the Buyer or the specific uses to which the product will be applied.